

# TECHNOWRAP H.P. PRS™

## GENERAL INFORMATION

---

Technowrap H.P. PRS™ is a high pressure pipeline repair system which has been designed for use on land. The system's intended application is for large diameters of pipe work, such as a 36 inch pipe operating at 170 bar pressure, and is ideally suited to the Middle East market. The uni-directional carbon based cloth applied with our epoxy resin system results in a faster application time.

Technowrap H.P. PRS™ is validated to ISO/TS 24817 and ASME PCC-2-2006 with Lloyd's Register "Type Approval" and all repairs come with a lifetime guarantee in excess of up to twenty years. Technowrap H.P. PRS™ can be applied on straight and slight bend pipe work.

## THE FACTS

---

Technowrap H.P. PRS™ is designed for the repair of internal assets and external assets suffering up to 80% wall loss. As with all Technowrap™ repair systems, Technowrap H.P. PRS™ can be used for pressures up to 250 barg/ 3625 psi and temperatures ranging from -75°C to +220°C/ -103 to 428°F.

## INSTALLATION

---

Repairs are applied by certified Technowrap™ Installers who are competent and experienced in the application and installation of Technowrap™ products within your specific industry/geography. With over 450 Technowrap™ Installers worldwide, we can ensure the successful and timely completion of your repairs.



**Walker Technical Resources Ltd**  
Scotstown Moor Base, Perwinnes Moss, Bridge of Don, Aberdeen, AB23 8NN  
**Tel** +44 (0)1224 822822 **Fax** +44 (0)1224 822299 **Email** info@wtr.uk.com

[www.wtr.uk.com](http://www.wtr.uk.com)